

How much cement can we do without?

Cyrille Dunant — William Shanks
London, September 2018



Outline

Introduction

Material Flows

Material Efficiency Measures


Conclusion

Introduction

- Mapping material flows
 - From raw materials to cement
 - From cement to applications
- Find out how much abatement potential there is
 - From cement technology improvement
 - From favouring certain design typologies
 - From optimising designs

How? — *Caveat emptor*


- Published data on production
- Expert interviews
- Modelling, Harmonising, verifying.




The typical uncertainty is around 8%

Material Flows


Cement Production




Material flows — Cement Production



Cement End Use



Material flows — Cement End Use



Material Efficiency Measures

Material Efficiency Measures

- Material Efficiency Measures chosen to represent a large fraction of the potential
- Cover construction methods, design, materials.
- Because for the first time we have a sufficiently precise material flow map, we can assess the abatement potential
- Abatement attribution depends on the order of method application

Material Efficiency Measures

- Post-tensioning
- Post-tensioned system can bear more load with less concrete

Material Efficiency Measures

- Post-tensioning
- Precast systems
- Post-tensioned system can bear more load with less concrete
- Precast member production can be better controlled, leading to more efficiency

Material Efficiency Measures

- Post-tensioning
- Precast systems
- Mix design
- Post-tensioned system can bear more load with less concrete
- Precast member production can be better controlled, leading to more efficiency
- In many cases real mix designs are significantly above the 250 kg/m³ limit

Material Efficiency Measures

- Post-tensioning
- Precast systems
- Mix design
- Calcined Clay + Limestone
- Post-tensioned system can bear more load with less concrete
- Precast member production can be better controlled, leading to more efficiency
- In many cases real mix designs are significantly above the 250 kg/m^3 limit
- Kaolinite-rich clays can be calcined and substitute up to 50% of the cement, and allow a further 15% substitution by ground limestone

Material Efficiency Measures


- Post-tensioning
- Precast systems
- Mix design
- Calcined Clay + Limestone
- Reduce construction waste
- Post-tensioned system can bear more load with less concrete
- Precast member production can be better controlled, leading to more efficiency
- In many cases real mix designs are significantly above the 250 kg/m^3 limit
- Kaolinite-rich clays can be calcined and substitute up to 50% of the cement, and allow a further 15% substitution by ground limestone
- Orders on site are always 4-5% above actual requirements

Material Efficiency Measures

- Post-tensioning
- Precast systems
- Mix design
- Calcined Clay + Limestone
- Reduce construction waste
- Optimised design
- Post-tensioned system can bear more load with less concrete
- Precast member production can be better controlled, leading to more efficiency
- In many cases real mix designs are significantly above the 250 kg/m^3 limit
- Kaolinite-rich clays can be calcined and substitute up to 50% of the cement, and allow a further 15% substitution by ground limestone
- Orders on site are always 4-5% above actual requirements
- Steel construction 'wastes' about 40% of the material. We estimate that savings of 20% are possible.


Curent and potential use

Reduction in cement demand due to each material efficiency technique, for each application in the UK




Curent and potential use

Reduction in cement demand due to each material efficiency technique, for each application in the UK




Curent and potential use

Reduction in cement demand due to each material efficiency technique, for each application in the UK




Curent and potential use

Reduction in cement demand due to each material efficiency technique, for each application in the UK



52% of emissions from cement use could be avoided


With no change in construction output



Conclusion

Directions for the future

- Why so much repairs?
- Can we design floor slabs better?
- Where is the cement unaccounted for used for?



Thank you

Thank you